



PP Camlock Coupling Type C

As the professional manufacture, we would like to provide you high quality PP Camlock Coupling Type C XunChi®. And we will offer you the best after-sale service and timely delivery.

Product Description

Male Adapter With Female Thread

Product Name: PP Camlock Coupling Type C XunChi®

Material: Polypropylene

Sizes: 1/2"-4"

MOQ: 50 PCS

Customizable contents: sizes, logo

Certificates: CE, ISO9001:2015

Competitive price

To learn more and get a quote, please leave your requirements on the form below.

Description:

Body materials: Polypropylene

Handle: stainless steel

Gaskets: Buna-N (NBR), EPDM

The thread of camlock fittings are BSP, BSPT, NPT

SIZE: 1/2" to 4"

Pressure :50-100 Psi (depending on size and temperature)

Operating temperature :-30-70°C (160°F)

When the temperature rises, the working pressure drops

Manufacture method: Injection molding

The use and connection way of cam and groove couplings: Type A camlock can usually be used with type D, type C, type B, type DC (Dust Cap) of the same size. To make a connection, simply slide the camlock adapter into the camlock coupling and with normal hand pressure, press the cam levers down.

Industry applications:

Industries: chemical, paint, agriculture, municipal, sewage

Applications: chemicals, solvents, varnishes, inks, fertilizers, wastewater

NingBo ZhenHai XunChi Hardware & Machine Co., Ltd.

Phone: +86-13566359033

E-mail: xcchina@xunchichina.com



www.xunchichina.com

NingBo ZhenHai XunChi Hardware & Machine Co., Ltd.
Phone:+86-13566359033
E-mail: xcchina@xunchichina.com